



Guangzhou Toksurvey Information Technology Co.,Ltd
www.toknav.cn | info@toknav.cn

Europe, North and South America
Tel and WhatsApp:
+1 (323) 847-7713 (Ian)

Asia, Africa and Oceania
Tel and WhatsApp:
+86 139 2607 5986 (Jeffrey)

No. 9 Caipin Road, Building B, Room 902-3, Huangpu District,
Guangzhou, China 510000

TOKNAV
www.toknav.cn

GNSS Application Solution PRODUCT BROCHURE



- GNSS Receiver Manufacturer
- Professional OEM&ODM
- Over 15 years experience in R&D and manufacturing

ABOUT US


Company Introduction

Guangzhou Toksurvey Information Technology Co., Ltd. was founded in 2019 by a team of R&D engineers. The company team has nearly 15 years of R&D background. At present, the company has nearly 2,500 square meters of office and factory, complete set of research equipment, and strong technical background.



Our company is committed to the R&D, production and sales of high-precision satellite positioning terminal products. More than 60% of the employees are engineers. Driven by technological innovation, the company maintains a steady growth rate of 60% every year.

At present, the company has successfully launched high-precision GNSS RTK (T5 series, T10 series, T20 series and T30 series), portable RTK receiver (P8 series), high-precision CORS station (NET660 series), data controller, GNSS antenna, and pre-marking robot to the market. We not only provide positioning products, but also provide a series of application solutions.



Our Targets



Make positioning more precise and easier.

Mission



Working together to improve global surveying quality.

Vision



To become a leader in the global surveying and mapping service.

Value



Your reliable supplier in positioning!

Slogan

Fields of Application

TOKNAV products can be widely used in precision surveying & mapping, mining operations, deformation monitoring, autonomous driving and other fields. We currently have a number of mature GNSS application solutions, such as deformation monitoring, CORS network, pre-marking robots, etc. TOKNAV products have passed CE, FCC, KC, NGS, IGS and other certifications, and are exported to more than 70 countries and regions around the world. Our products are well received in the global market, and now we have become a system integration supplier in the global market.



Construction



Monitoring



Mapping & GIS



Surveying



Agriculture



Marine

Certifications

Antenna Calibrations						
National Geodetic Survey						
Browse Antenna Information by Company Brand and Model Access Calibrations for All Antennas Help Links						
Toknav						
Individual calibrations for Antennas						
NOTE: Expand an ARP or NRP abbreviation						
Antenna Code						
TNAV10PRO						
TNAV20						
TNAV20PRO						
TNAV5						
TNAV5LITE	NONE	Drawing Label Size	ANTEX ANTINFO	Toknav T5LITE w/integrated antenna	04-JAN-24	BAM

CONTENT

Products

Deformation Monitoring	1
CORS and VRS Service	3
Marking Robot	5



Deformation Monitoring

The GNSS based monitoring system is widely applied in the fields of landslide geological hazard monitoring, dam deformation monitoring, mining area surface subsidence monitoring, tailings reservoir deformation monitoring, bridge deformation monitoring and high-rise building deformation monitoring and other fields with potential safety hazards, which can effectively prevent and avoid disasters and ensure safety of important facilities and people's property.

Characteristic



Flexible control

There is no need for line-of-sight between the stations, and the positioning options are flexible.



High real-time

For the collected data, output data results in real time.



Simple operation platform

Easy to operate, data is intuitive and easy to understand.




Automatic monitoring


Automatic acquisition, processing, analysis and early warning of horizontal displacement and vertical displacement.




Product Mix



Product Schematic Diagram




Platform Display




Login interface



Position display



Monitoring




Device management

VRS Service

Definition

VRS is a kind of Network Real Time Kinematic (NRTK) technology.

- VRS generate and provide a virtual reference station data near user's position based on the regional real reference station for user to calculate RTK.
- VRS requires 3G/4G/5G to support communication.



Features & Benefits

- Instant access to RTK corrections.
- Centimeter-accurate corrections tailored to your geographic location.
- Built-in redundancy to ensure connectivity, consistency and quality.
- Cost-effective and simple to use.
- Professionally-managed and secure.
- Streamlined workflows, done right the first time.

Working Principle

Definition

We provide instant access to RTK corrections using a CORS GNSS network, proprietary software platform and VRS service monitoring platform.

VRS SERVICES

Monitoring Platform

Software Platform

CORS GNSS Network

Application Areas



Advantage of Our Technology

Full-stack self-developed software and hardware technology


- The algorithms, software, and hardware used in our VRS service are independently developed.

Meeting various high-precision application needs


- Includes surveying users, agricultural drones for crop protection, building monitoring, geological disaster monitoring, car lane-level navigation, electric bicycles, and other types of users.

Ability to serve a massive number of users

- Data management, data processing, and user services are independent of each other through a data bus.
- Not only possesses powerful service capabilities of individual servers, but also supports a massive number of concurrent users through server expansion.




Capability of satellite-based and ground-based fusion processing



- Capable of satellite-based and ground-based fusion processing, enabling network RTK and PPP-RTK fusion processing.
- Ensures high-performance positioning in low-latitude area through processing multi-GNSS data and refining ionospheric models.

Platform Display



Base station network

Device management

Marking Robot

The TR10Pro Line Marking Robot is an auxiliary work robot capable of automatically measuring, marking, and drawing lines. It is equipped with an adjustable-width nozzle, making it suitable for various application scenarios such as sports fields, highways, municipal roads, airport runways, and more. The software comes with a variety of built-in templates, including sports field designs, icons, arrows, and numbers, while also supporting user-defined editing or template importing. This significantly improves the efficiency of road marking, pre-marking, and spray printing, while reducing labor pressure and costs.



Characteristic



High-precision Positioning

The TR10Pro supports full constellation and full band frequency signal tracking with 1408 channels. Its antenna can simultaneously receive signals from BDS, GPS, GLONASS, GALILEO, SBAS, and QZSS satellites, enabling full constellation positioning. The robot also supports Real-Time Kinematic(RTK) differential positioning and can access the Beidou ground-based augmentation system for high-precision positioning. By combining high-precision positioning with robotic operations, it achieves reliable and repeatable centimeter-level line marking accuracy.



Long Battery Life and High Speed

The TR10Pro is equipped with a built-in 24V/20Ah lithium battery, offering a top speed of 3.6km/h, a range of 28.8km, and a battery life up to 8 hours.



Multi-functional

The TR10Pro can accommodate different sizes of spraying devices and can achieve different types of markings, such as dots, lines, curves, numbers, letters, and patterns. It has built-in models of various sports fields, such as soccer, tennis courts. It supports custom editing of sports field models and is easy to use.



High Adaptability

The TR10Pro is compact and equipped with two 200W hub motors, enabling it to perform operations smoothly on rough surfaces like grass and gravel roads, with the ability to make sharp turns and climb slopes up to 20 degrees.



Easy to Operate


Combining a controller with an Android tablet and our custom-developed app allows field operators to easily learn and operate the device with minimal training.




Supports Multiple File Formats

The app supports various file formats, including dxf, csv etc., enabling the robot to follow designed construction plans for seamless implementation.

Application



Sport fields



Measurement guidance



Highway



Parking lot




Special marking



Municipal road

System Architechure



System



Physical

- Dimensions L*W*H: 692mm*982mm*649mm (Removable side scribing mechanism with a width of 388mm)
- Wheelbase: 400mm
- Wheel Track(mm): 465mm
- Weight: 36kg



Battery

- Battery type: Lithium 24V/20Ah
- Battery Life: 8 hours
- Endurance: 28.8km



Environment

- Communication: CAN
- Operating temperature: -10℃~60℃
- Storage temperature: -10℃~45℃
- IP rating: IP3X



Mobility

- Motor specification: 200W*2
- Maximum speed(m/s): 1m/s
- Minimum turning radius: 0°(Turn in place)
- Maximum climbing ability: 20°



Performance

- Speed: 1km/s
- Materials: Latex paint/Titanium white slurry
- Hopper capacity: 10L
- Accuracy: ≤1.5cm
- Line types: Dots, lines, curves, numbers, letters, patterns.
- Sports Field Type: Running track, tennis court, soccer field, (Field Marking) football field, lacrosse court, baseball field
- Drawing Width: 5cm-15cm adjustable side nozzle (Field Marking)